



Kirk Sandall Industrial Estate, Doncaster, South Yorkshire, DN3 1QR

+44 (0)1302 310 113
 enquiries@prosolveproducts.com
 www.prosolveproducts.com

ProSolve is trademark of S.T.L Trading Company Limited
 Reg in England No: 5230722
 VAT Reg No: 381 3533 58

DATA SHEET

Underground Warning Tape

TYPES

Code	Name
CCTVT	PROSOLVE UNDERGROUND WARNING TAPE - CCTV (GREEN)
COMMST	PROSOLVE UNDERGROUND WARNING TAPE - COMMUNICATIONS (GREEN)
DATAT	PROSOLVE UNDERGROUND WARNING TAPE - DATA CABLE (GREEN)
ELECT	PROSOLVE UNDERGROUND WARNING TAPE - ELECTRIC CABLE (YELLOW)
FIBREOT	PROSOLVE UNDERGROUND WARNING TAPE - FIBRE OPTIC CABLE (GREEN)
FIREMAINT	PROSOLVE UNDERGROUND WARNING TAPE - FIRE MAIN (RED)
GAST	PROSOLVE UNDERGROUND WARNING TAPE - GAS MAIN (YELLOW)
RISINGMT	PROSOLVE UNDERGROUND WARNING TAPE - RISING MAIN (GREEN)
SEWERT	PROSOLVE UNDERGROUND WARNING TAPE - SEWER PIPE (RED)
SEWERPUMPT	PROSOLVE UNDERGROUND WARNING TAPE - SEWERAGE PUMPING MAIN (RED)
SPRINKLERT	PROSOLVE UNDERGROUND WARNING TAPE - SPRINKLER (BLUE)
STORMDT	PROSOLVE UNDERGROUND WARNING TAPE - STORM DRAIN (GREEN)
STREETLT	PROSOLVE UNDERGROUND WARNING TAPE - STREET LIGHTING CABLE (YELLOW)
SURFWT	PROSOLVE UNDERGROUND WARNING TAPE - SURFACE WATER (BLUE)
TELT	PROSOLVE UNDERGROUND WARNING TAPE - TELEPHONE CABLE (GREEN)
TRAFFICT	PROSOLVE UNDERGROUND WARNING TAPE - TRAFFIC SIGNAL (YELLOW)
WATERT	PROSOLVE UNDERGROUND WARNING TAPE - WATER PIPE (BLUE)
STREETLTPUR	PROSOLVE UNDERGROUND WARNING TAPE-STREET LIGHTING CABLE (PURPLE)

DESCRIPTION

- Premium and economy grades available, premium manufactured in accordance with ENATS 12-23 Issue 2:2013
- High quality linear low density polyethylene with lead-free
- pigments used with both premium and economy grades.
- Soil PH tolerance is 2.5 to 11.0 inclusive.

FEATURES:

Material: Low Density Polyethene (LLDPE)

Country of Origin: United Kingdom

Description: Single wound sheet (sws) treated for 1 side print

Sizes/Widths: 150mm x 100m/250m/365m/1000m

Thickness: Economy 0.5 micron / Premium 0.1mm

Slip Level: Low

Shrink: N/A

Base Colour: Various

Ink: Highly resistant, solvent based

Core: 76mm diameter cardboard core

Reel Weight: Nominal

Tolerance: As per our current house standards +/- 10%

IMPORTANT NOTICE

All statements, technical information and recommendations are based on tests we believe to be reliable as at the date of hereof, but the accuracy or completeness thereof is not guaranteed. Please ensure before using the product that it is suitable for your intended use. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, other than for fraudulent misrepresentation, ProSolve expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT.